

CSR-1000 CONCRETE BONDER PREMIXED ACRYLIC FORMULATION

DESCRIPTION

CSR-1000 CONCRETE BONDER is a premixed acrylic formulation of a high quality butyl acrylic copolymer. Additional modifiers are incorporated to enhance the over-all strength potential as a concrete overlay system when used with CenturyStone cement/aggregate blends (i.e. CS-100, 500).

SOLIDS CONTENT: 100% ACRYLIC.

TYPICAL USES

CSR-1000 CONCRETE BONDER is an integral component in the CenturyStone Concrete Repair and Decorative Coating System.

When combined with CS-100 AGGREGATE BASE or CS-500 AGGREGATE TEXTURE the overlay can be applied as a base-coat, an acrylic lace texture, or various other trowelled finishes (i.e. tile, brick, flagstone, etc.) over properly prepared existing concrete substrates.

METHODS OF APPLICATION

As part of a complete overlay system, the CSR-1000 CONCRETE BONDER combined with CS-100 and 500 AGGREGATE blends can be applied by trowel, squeegee, screed, broom, brush or sponge. The consistency can be altered for a variety of repair or overlay applications.

PRIMARY FEATURES (as part of complete system)

- High Performance Concrete Technology
- 2" to Zero application thickness
- Re-pitch concrete surfaces (trip hazards, etc.)
- All-purpose base-coat
- Slip-resistant top coat (i.e. broom finish)
- Repairs broken concrete edges and spalls
- Cool walking surfaces
- Unlimited Decorative Applications
- Compatible with acrylic-based products
- Minimal drying time
- Suitable for interior or exterior
- High abrasion resistance

APPLICATION INSTRUCTIONS

DO NOT ADD WATER.

Add 1-2 gallons CSR-1000 CONCRETE BONDER to 1-50# bag of CS-100 or 500 AGGREGATE blends. Mix in a clean bucket with an electric operated masonry mixing paddle. Rinse off mixing paddle and tools with water immediately after use. Apply CSR-1000 to substrate as a primer before application. Do not install at ambient temperatures below 40 degrees F.

COVERAGE

Coverage will vary with applications.

PACKAGING

5-gallon bucket
Pallet (36 buckets)

